



FACT SHEET

Water Level Meter

The Water Level Meter uses a 16mm probe to measure depths in wells to an accuracy of 3mm.



Reliable and accurate measurement of groundwater levels

Features

- Available in 30m, 60m and 100m lengths
- Lightweight steel and aluminum storage reel for easy transportation and durability in the field
- Audible and visible alarms activated on reel when probe contacts water
- Accurate Polyethylene coated steel tape marked in mm increments
- Fully field replaceable probe is only 16mm in diameter
- Water resistant padded carrying case to protect instrument
- Adjustable sensitivity to prevent false triggering
- When combined with a Geocontrol Pro & Bladder Pump an auto shut-off for low flow sampling is available.

Accessories

- 12050060 Leader guard - protects tape from sharp well edges.

Specifications

- Size: Reel 33cm H x 28cm W x 18cm D
Probe 1.59cm O.D. x 15.56cm L
- Length & Weight: 30 meters = 9 lbs. (4 kg)
60 meters = 11 lbs. (5 kg)
100 meters = 14 lbs. (6.3 kg)
- Material: Reel - Polypropylene and aluminum (ET)
Tape - Polyethylene coated steel
Probe - Teflon® and stainless steel
- Power: 9 Volt DC alkaline battery
- Alarm: Audible and visual
- Certifications: CE Rated