

FACT SHEET

Water Level Meter

Reliable and accurate measurement of groundwater levels in boreholes, monitoring wells and tanks.



Robust construction for accurate measurement in field conditions

Features

- Simple, fast & easy to use
- Robust construction and light in weight
- Available as standard in 30m, 50m, 60m & 100m lengths and longer, to order
- Audible and visible alarms activated on reel on water contact
- No disturbing parts when inserted into a borehole
- Variable cable lengths from 5 to 1,000 metres
- 15mm diameter probe
- Two-year warranty.
- Available in 4 styles:
 - Type 10 on Plastic Frame
 - Type 15 Handheld, no Frame
 - Type 20 Mini Handheld, no Frame
 - Type 25 on Metal Frame.



Accessories

- 12050060 Leader guard - protects tape from sharp well edges
- Bottom sensor available for additional sounding of drilling depth
- 10mm probe, length 140mm.

Specifications

- | | |
|--|---|
| <ul style="list-style-type: none"> • Measuring probe materials: • Measuring probe dimensions: • Power supply: • Operating temperature range: • Recommended storage temperature: • Safety class for probe/td>: • Safety class measuring tape drum: • Measuring tape: | <p>Stainless steel and electroplated brass, easy to clean Ø 15 mm, length 195 mm; Ø 12 mm, length 70 mm 4 x 1.5 V batteries / size C; 1 x 9 Volt 30 °C up to +75 °C +5 °C up to +30 °C, for battery protection IP 68, permanently pressure resistant IP 64, spray water resistant.</p> <ul style="list-style-type: none"> - Bifilar strip made of white polyethylene with 2 stainless steel wires - Resistant to ultraviolet rays and to contaminated or salt water - Metres printed in red; cm divisions and dm figures in black. |
|--|---|