

# FACT SHEET

## Total Fluids Pump "Reclaimer"

The Total Fluids Pump is an externally controlled compressed air operated purging and remediating pump.



### Purging and developing wells in aggressive environments

#### Advantages

- Pumps to depths of 75m or more in 2" diameter or larger wells
- Easy to clean and maintain - pump has no moving parts
- Pumps both product and water from contaminated wells
- Pumps suspended solids in water
- Intrinsically safe design - pump operates on compressed air.

#### Disadvantages

- Cannot be used as a sampling pump
- Needs external controller and air compressor.

#### Accessories

- Geocontrol 2 controller unit
- External air compressor
- 12.20.04 6x8mm Polyethylene air delivery tube
- 12.20.13 10x12mm Polyethylene product retrieval tube
- Optional safety rope/cable.

#### Specifications

- 42mm diameter
- Pumps up to 11 litres per minute
- Pumps down to 75m or more
- Length 62 or 122cm
- Stainless Steel construction.

#### Alternatives

For a groundwater pump that can pump to similar depths and also be used as a sampling pump you might like to consider the Grundfos MP1 pump. For controller-less pumping a Total Fluids Pump "Auto Reclaimer" might be an option. The Geocontrol 2 and air compressor can also be used with a portable bladder pump as well as the Total Fluids Pump for a total sampling and purging solution.